

## SAFETY DATA SHEET

REVISION DATE: 05-01-2015 SUPERSEDES: 02-06-2015

### SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER

PRODUCT INFORMATION

PRODUCT: FOSTER 40-50 (FD4050)

PRODUCT DESCRIPTION: Coating INTENDED USE: Coating PRODUCT IDENTIFIER: 820379PM

COMPANY INFORMATION

H.B. Fuller Construction Products Inc.

1105 S. Frontenac Street

Aurora, IL 60504

Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

## **SECTION 2: HAZARDS IDENTIFICATION**

GHS Hazard Symbols:







GHS Signal Word: Danger

GHS Classification: Skin Sensitisation Category 1; Germ Cell Mutagenicity Category 1B; Hazardous to the

aquatic environment - Acute Category 2; Hazardous to the aquatic environment - Chronic

Category 2

GHS Hazard May cause an allergic skin reaction.; May cause genetic defects..; Toxic to aquatic life..;

**Phrases:** Toxic to aquatic life with long lasting effects.

**GHS Precautions:** 

Safety Precautions: Obtain special instructions before use. Do not handle until all safety precautions have

been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face

protection.

First Aid Measures: IF ON SKIN: Wash with plenty of soap and water. IF exposed or concerned: Get medical

advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash

contaminated clothing before reuse. Collect spillage.

Storage: Store locked up.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international

regulation for hazardous wastes.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	PERCENT	Classification	Note
Barium compound	13701-59-2	5 - 10	Acute Tox. 4; H332 Acute Tox. 4; H302	* (see below)
Titanium dioxide	13463-67-7	1 - 5	Carc. 2; H351	* (see below)



## SAFETY DATA SHEET

Zinc oxide	1314-13-2	1 - 5	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	
lodo-2-propynyl butylcarbamate	55406-53-6	0.1 - 1	Aquatic Acute 1; H400 Acute Tox. 4; H332 Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335	

<sup>\*</sup>This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

## **SECTION 4: FIRST AID MEASURES**

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

# **SECTION 5: FIRE FIGHTING MEASURES**

EXTINGUISHING MEDIA:

UNUSUAL FIRE AND EXPLOSION HAZARDS:

SPECIAL FIRE FIGHTING INSTRUCTIONS:

**HAZARDOUS COMBUSTION PRODUCTS:** 

Use water spray, foam, dry chemical or carbon dioxide.

There is a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers.

Persons exposed to products of combustion should wear selfcontained breathing apparatus and full protective equipment. Carbon dioxide, Carbon monoxide Metal fumes Silicon dioxide

carbon dioxide, Carbon monoxide Mean fames officen dioxi

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

SPECIAL PROTECTION: No adverse health effects expected from the clean-up of spilled material.

Follow personal protective equipment recommendations found in

Section 8 of this MSDS.

METHODS FOR CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to

containers for disposal. Keep spilled product out of sewers, watersheds,

or water systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

# **SECTION 7: HANDLING AND STORAGE**

Handling: No special handling instructions due to toxicity.



## SAFETY DATA SHEET

Storage: Store in a cool, dry place. Protect from freezing

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Consult the Technical Data Sheet for specific storage instructions.

### **EXPOSURE LIMITS:**

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Titanium dioxide	* (see below)	10 mg/m3 TWA	15 mg/m3 TWA (total dust)
Zinc oxide		2 mg/m3 TWA (respirable fraction) 10 mg/m3 STEL (respirable fraction)	5 mg/m3 TWA (fume); 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
Amorphous silica	* (see below)	No data available.	20 mppcf TWA; ((80)/(% SiO2) mg/m3 TWA)

<sup>\*</sup>This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

#### **ENGINEERING CONTROL METHODS:**

VENTILATION: Use local exhaust ventilation or other engineering controls to

minimize exposures.

EYE PROTECTION: Wear safety glasses when handling this product.

SKIN PROTECTION: Not normally required. Wear chemically resistant gloves to prevent

prolonged or repeated contact.

GLOVES: Not normally required. Use nitrile gloves if conditions warrant.

RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when

handling this product. Use a respirator if general room ventilation is

not available or sufficient to eliminate symptoms.

Respirators should be selected by and used following requirements

found in OSHA's respirator standard (29 CFR 1910.134).

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE: Liquid COLOR: White ODOR: Mild Sweet **ODOR THRESHOLD:** Not established Not established FREEZING/MELTING POINT (deg. C): Not established **BOILING POINT (deg. C):** Not established FLASH POINT: Non flammable **EVAPORATION RATE:** Not established

FLAMMABILITY: Not a flammable solid or gas

UPPER EXPLOSIVE LIMIT (% in air):

LOWER EXPLOSIVE LIMIT (% in air):

VAPOR PRESSURE (mm Hg):

VAPOR DENSITY:

Not established

Not established

Not established

WEIGHT PER GALLON (lbs.): 11.80 SPECIFIC GRAVITY: 1.360

SOLUBILITY: Not established



## **SAFETY DATA SHEET**

OCTANOL/WATER COEFFICIENT:

AUTOIGNITION TEMPERATURE:

DECOMPOSITION TEMPERATURE:

VISCOSITY:

Not established

Not established

Not established

Not established

Not established

SOLIDS (% by weight): 56.0 VOC, weight percent 1.43

VOC, U.S. EPA Method 24, less water and exempt

solvents (theoretically determined)

38.1g/liter of material

# **SECTION 10: STABILITY AND REACTIVITY**

STABILITY: Stable under normal conditions.

CHEMICAL INCOMPATIBILITY: Not established HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide Metal fumes

Silicon dioxide

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Component Toxicity / Toxicology Data:

COMPONENT NAME	LD50/LC50		
Water	ORAL LD50 RAT > 90 ML/KG		
Barium compound	ORAL LD50 RAT 530 MG/KG		
	DERMAL LD50 RABBIT > 2,000.00 MG/KG		
Titanium dioxide	ORAL LD50 RAT > 10,000 MG/KG		
Zinc oxide	ORAL LD50 RAT > 5,000 MG/KG		
Amorphous silica	ORAL LD50 RAT > 5,000 MG/KG		
•	INHALATION LC50-1H RAT > 2.20 MG/L		
	DERMAL LD50 RABBIT > 2,000.00 MG/KG		
Propylene glycol	ORAL LD50 RAT 20,000 MG/KG		
•	DERMAL LD50 RABBIT 20,800,00 MG/KG		

# This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: Can cause minor skin irritation, defatting, and dermatitis. Serious eye damage / irritation: Can cause minor irritation, tearing and reddening.

Respiratory / skin sensitization: No data available. Germ cell mutagenicity: May cause genetic defects.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: No data available.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: May cause respiratory irritation.

Specific target organ toxicity-repeated exposure: No data available.

Target organs potentially affected by exposure: Lungs

Aspiration hazard: No data available.

Medical Conditions Aggravated by Exposure: Lung disease



## SAFETY DATA SHEET

## **SECTION 12: ECOLOGICAL INFORMATION**

OVERVIEW: No ecological information available for this product.

MOBILITY: No data available. PERSISTENCE: No data available. BIOACCUMULATION: No data available.

### This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:
Amorphous silica	Acute Toxicity (Fish): 96 Hr LC50 Brachydanio rerio: 5000 mg/L [static]
	Acute Toxicity (Daphnia): 48 Hr EC50 Ceriodaphnia dubia: 7600 mg/L
	Acute Toxicity (Algae): 72 Hr EC50 Pseudokirchneriella subcapitata: 440 mg/L
Propylene glycol	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: 51600 mg/L [static]; 96 Hr
1	LC50 Oncorhynchus mykiss: 41 - 47 mL/L [static]; 96 Hr LC50 Pimephales promelas:
1	51400 mg/L [static]; 96 Hr LC50 Pimephales promelas: 710 mg/L
	Acute Toxicity (Daphnia): 24 Hr EC50 Daphnia magna: >10000 mg/L; 48 Hr EC50
	Daphnia magna: >1000 mg/L [Static]
	Acute Toxicity (Algae): 96 Hr EC50 Pseudokirchneriella subcapitata: 19000 mg/L

### **SECTION 13: DISPOSAL CONSIDERATIONS**

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

### **SECTION 14: TRANSPORT INFORMATION**

Consult Bill of Lading for transportation information.

US DOT: NOT REGULATED NOT REGULATED

IMDG: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES,

LIQUID, N.O.S. (ZINC OXIDE), 9, III, MARINE POLLUTANT

## **SECTION 15: REGULATORY INFORMATION**

**INVENTORY STATUS** 

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's

Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt

from DSL requirements.

EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product

cannot be imported into Europe unless the REACH requirements are

met.

AUSTRALIA AICS: This product is in compliance with the Australian Inventory of

Chemical Substances requirements.

KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List

requirements.

CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical

Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement



## **SAFETY DATA SHEET**

Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg.request@hbfuller.com to request an export review.

This product contains a chemical substance that is subject to a Significant New Use Rule (SNUR) under Section 5(a)(2) of TSCA:

.alpha.-(4-Nonylphenyl)-.omega.-hydroxy-poly(oxy-1,2-ethanediyl)

79 FR 59186, Oct 1, 2014 (Proposed rule)

### FEDERAL REPORTING

**EPA SARA Title III Section 313** 

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	1 %
Barium compounds	13701-59-2	5 - 10
Zinc compounds	1314-13-2	1 - 5
3-lodo-2-propynyl butylcarbamate	55406-53-6	0.1 - 1

#### STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List		CAS	Percent
Titanium dioxide	(Carcinogen)	13463-67-7	1 - 5
Formaldehyde	(Carcinogen)	50-00-0	0.001 - 0.01
Acetaldehyde	(Carcinogen)	75-07-0	< 10 ppm
Arsenic compounds (inorganic)	(Carcinogen)	7440-38-2	< 10 ppm
Lead compounds	(Carcinogen)		< 10 ppm

## Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's.

- 4-Nonylphenol, ethoxylated
- 4-Nonylphenol, ethoxylated

### **SECTION 16: OTHER INFORMATION**

SDS VERSION DATE:

05-01-2015

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 0 FLAMMABILITY -- 0 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment

recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B.Fuller Construction Products, Inc. from its suppliers, and because H.B.Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B.Fuller



# SAFETY DATA SHEET

Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B.Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B.Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.